

ALL PRODUCT DIMENSIONS ARE BEFORE COATING

REFERENCE DRAWING ONLY - NOT TO BE USED FOR INSPECTION PURPOSES

DO NOT SCALE

MATERIAL SPECIFICATION

END RING (Part 1)
STEEL to
BS EN10025-2 GRADE S275JR
CENTRE SLEEVE (Part 2)
STEEL to
BS EN10025-2 GRADE S275JR
GASKET (Part 3)
RUBBER 80 HARDNESS
Grade to suit service
BOLTS (Part 4)
STEEL BS EN ISO898-1
PROPERTY CLASS 4.8
NUTS (Part 5)
STEEL BS4190
GRADE 4
WASHERS (Part 6)
STAINLESS STEEL BS1449:PART 2
GRADE 304S15


FINISH SPECIFICATION

NOTES


Locating Plugs/Pin Register
If Locating Plugs/Pins are required,
3 are to be supplied.

BOLT TORQUES

Torque to 95-120Nm



ISOMETRIC VIEW



Pipe O.D. includes a Coating of 1.50mm thick Un-Coated Pipe is 1067mm O.D.

PIPE O.D.	PIPE MATERIAL	PIPE TOLERANCE		BOLTS	GASKET MOULD	WORKING PRESSURE	TEST PRESSURE	WEIGHT KG	ASSEMBLY DRG NO
		+	-						
1070.00	STEEL	1.60	1.60	14-M16x265	J72LS	17.6bar	26.5bar	98.88	7879_1118

OVERALL DIMENSIONS DRAWING
FOR REFERENCE ONLY
VIKING JOHNSON RESERVE THE
RIGHT TO AMEND DETAILS WITHOUT
PRIOR NOTIFICATION

This drawing is the exclusive property of VIKING JOHNSON and
is confidential and must not be reproduced or disclosed to a third
party without written consent. It must be used only for the
purpose which it has been issued and is returnable on request.

CRANE A Crane Co Company



OVERALL DIMENSIONS OF
VIKING JOHNSON COUPLING ASSEMBLY
'YF2' SECTION
FOR 1067.00mm O.D. PIPE

RELEASE LEVEL: Released

SHEET 1 OF 1



DRAWN	AUTO	SCALE	1:250
DATE	15/08/18	GENERIC	7879

DRG NO SKP12605-1