

# ALL PRODUCT DIMENSIONS ARE BEFORE COATING

REFERENCE DRAWING ONLY - NOT TO BE USED FOR INSPECTION PURPOSES

DO NOT SCALE

## MATERIAL SPECIFICATION

**FLANGE ADAPTOR (Part 1)**  
Ductile Iron to BS EN1563:1997  
Symbol EN-GJS-450-10  
**END RING (Part 2)**  
Ductile Iron to BS EN1563:1997  
Symbol EN-GJS-450-10  
**CARRIER (Part 3)**  
Acetal Co-polymer Grade C2521  
or equivalent  
**GRIPPER (Part 4)**  
Acetal Co-polymer Grade C9021  
or equivalent  
**GASKET (Part 5)**  
Rubber (70 IRHD)  
Grade to suit service  
**BOLTS (Part 6)**  
Stainless Steel to BS EN ISO3506-1:2009  
Grade A2 Property Class 70 or  
Grade A2 Property Class 80 or  
Grade A4 Property Class 70 or  
Grade A4 Property Class 80  
**NUTS (Part 7)**  
Stainless Steel to BS EN ISO3506-2:2009  
Grade A4 Property Class 80  
**WASHERS (Part 8)**  
Stainless Steel to BS1449:Part 2:1983  
Grade 304S15 or  
Stainless Steel to BS EN ISO3506-1:2009  
Grade A2 Property Class 50 or  
Grade A4 Property Class 50  
**'O' SEAL GASKET (Part 9)**  
As specified by order

## FINISH SPECIFICATION

**FLANGE ADAPTOR (Part 1)**  
Rilsan Nylon II  
**END RING (Part 2)**  
Rilsan Nylon II  
**BOLTS (Part 6)**  
Dry Film Lubricant  
**NUTS (Part 7)**  
Dacromet 500

## NOTES

### Bolt Torques

M12 = 55-70Nm

### Pipe Materials

#### Gripping and Non-Gripping (Flex)

Used without support liner

Steel

Ductile Iron

Cast Iron

PVC Class 4 DIN8062

Used with support liner

PE80



PE100

PVC - all other classes

#### Non-Gripping (Flex)

Used without support liner

Asbestos Cement



NOM SIZE	SIZE RANGE	FLANGE DRILLING	WORKING PRESSURE				NO OFF CARRIERS	NO OFF GRIPPERS	GASKET MOULD	BOLTS NO-SIZExLEN	INSERTION DEPTH		WEIGHT KG	ASSEMBLY DRG NO
			WATER		GAS						MIN	MAX		
			GRIPPING	FLEX	GRIPPING	FLEX								
40	43.5-63.5	50 PN10,16	16bar	16bar	5bar	5bar	22	22	13127_2	3-M12x70	65	110	4.5	13199_1

OVERALL DIMENSIONS DRAWING  
FOR REFERENCE ONLY  
VIKING JOHNSON RESERVE THE  
RIGHT TO AMEND DETAILS WITHOUT  
PRIOR NOTIFICATION

This drawing is the exclusive property of VIKING JOHNSON and  
is confidential and must not be reproduced or disclosed to a third  
party without written consent. It must be used only for the  
purpose which it has been issued and is returnable on request.

CRANE A Crane Co Company

OVERALL DIMENSIONS OF  
ULTRAGRIP FLANGE ADAPTOR  
FOR 43.5-63.5mm O.D. PIPE RANGE  
WITH 50 PN10,16 FLANGE

RELEASE LEVEL: Concept

SHEET 1 OF 1

**VIKING JOHNSON**  
World leaders in pipe joints and repair products

DRAWN	P.N.	SCALE	1:500
DATE	03-Mar-10	GENERIC	O.DIM.13199.1.2

DRG NO O.DIM.13199.1.2