



--	--	--

MATERIAL SPECIFICATION		
END RING (Part 1)		
Steel to BS EN10025-2		
Grade S275JR		
CENTRE SLEEVE (Part 2)		
Steel to BS EN10025-2		
Grade S275JR		
GASKET (Part 3)		
70 & 80 IRHD EPDM to BS EN681-1 or		
70 & 80 IRHD Nitrile to BS2494		
INSERT (Part 4)		
Stainless Steel to BS3146		
Grade ANC2		
BOLT (Part 5)		
Steel to BS EN ISO898-1		
Property Class 8.8		
NUT (Part 6)		
Steel to BS EN29898-2		
Grade 8.0		
WASHER (Part 7)		
Stainless Steel to BS1449:Part 2		
Grade 304S15		

7	WASHER	6
6	NUT	6
5	BOLT	6
4	INSERT	14
3	GASKET	2
2	CENTRE SLEEVE	1
1	END RING	2
PART	DESCRIPTION	NO OFF
LIST OF PARTS		



PIPE O.D.	TOLERANCE ON O.D.	BOLTS No-ØxLEN	GASKET MOULD	INSERT NOxTYPE	WEIGHT KG	PRESSURE (bar)		ASSEMBLY DRG NO
						WORKING	TEST	
165.1	+1.6 -0.8	6-M12x170	1369	7 x B	9.2	16	24	7561/9

OVERALL DIMENSIONS FOR REFERENCE ONLY VIKING JOHNSON RESERVE THE RIGHT TO AMEND DETAILS WITHOUT PRIOR NOTIFICATION		TITLE OVERALL DIMENSIONS OF FLEXLOCK COUPLING FOR FOR 165.1mm O.D. PIPE		<div>VIKING JOHNSON <i>World leaders in pipe joint's and repair products</i></div>	
This drawing is the exclusive property of VIKING JOHNSON and is confidential and must not be reproduced or disclosed to a third party without written consent. It must be used only for the purpose which it has been issued and is returnable on request.		DRAWN		CAD	DATE 21:11:97
		SCALE N.T.S.		P.N.	APPROVED
		CHECKED			
CRANE A Crane Co Company				DRG NO. SKC22984-1	
©				ISSUE B	