 DO NOT SCALE

12 HOLES Ø23 FOR M20
BOLTS ON 295 PCD

Steel to BS EN10025-2
Grade S275JR

Steel to BS EN10025-2
Grade S275JR

70 IRHD EPDM to BS EN681-1 or
70 IRHD Nitrile to BS2494



Stainless Steel to BS3146
Grade ANC2

Steel to BS EN ISO898-1
Property Class 8.8

Steel to BS EN 20898-2
Grade 8.0

Stainless Steel to BS1449:Part 2
Grade 304S15

Rubber



PIPE O.D.	PIPE MATL	FLANGE DRILLING	TEE-BOLTS	GASKET MOULD	GASKET INSERT	WORKING PRESSURE	TEST PRESSURE	WEIGHT	ASSEMBLY DRG NO
219.1	STEEL	200 PN16	12-M12x115	1370	12 x B	16bar	24bar	15.2KG	7660/13

VIKING JOHNSON RESERVE THE
RIGHT TO AMEND DETAILS
WITHOUT PRIOR NOTIFICATION

This drawing is the exclusive property of VIKING JOHNSON and is confidential and must not be reproduced or disclosed to a third party without written consent. It must be used only for the purpose which it has been issued and is returnable on request.

CRANE A Crane Co Company

TITLE OVERALL DIMENSIONS OF
FLEXLOCK FLANGE ADAPTOR
FOR 219.1mm O.D. PIPE
WITH 200 PN16 FLANGE



DRAWN	CAD	DATE 2:8:07
SCALE N.T.S.	P.N.	APPROVED
CHECKED		
DRG NO. SKC26368-1		ISSUE B